

## ساب بوكسى EP- 704

دهان أيبوكسى مقاوم للتآكل والصدأ للحديد والصلب

### الوصف:

- ساب بوكسى EP- 704 عبارة عن دهان ايبوكسى على هيئة مركبين بإضافات تزيد مقاومة الحديد للتآكل والصدأ .
- يمكن استخدام ساب بوكسى EP- 704 لحماية حديد التسليح للخرسانة من الصدأ وللحصول على التصاق أقوى بين الخرسانة وحديد التسليح ، والسيارات ، وحماية الأسطح المعدنية من الصدأ .

### المواصفات الفنية:

- المواد الصلبة : 80 %
- اللون : رمادي وملون
- نسب الخلط : 6 أ : 1 ب بالوزن
- فترة التشغيل : 60 دقيقة في درجة 20 ° م
- معدل الاستهلاك : 300 جرام / م<sup>2</sup> وجه

### طريقة التشغيل:

- يخلط مركبي ساب بوكسى EP- 704 خلطا جيدا قبل التشغيل مباشرة .
- يمكن دهانه بالفرشاة أو الرولة .
- يفضل دهان وجهين من ساب بوكسى EP- 704 على أن يدهن الوجه الثاني بعد 6 ساعات على الأقل من دهان الوجه الأول .

### مدة التخزين :

- عام في العبوات المغلقة

### العبوات:

- مجموعة 1 كجم ، 5 كجم .
- يتم الخلط بالوزن طبقا لما هو مدون على العبوات .

لمزيد من المعلومات برجاء الاتصال بخدمة الدعم الفني

## **SAP POXY EP- 704**

### Zinc Epoxy & Anti Corrosion Coating for Iron & Steel

#### **DESCRIPTION:**

- **SAP POXY EP- 704** is 2 component epoxy paint modified with zinc to provide the highest protection against corrosion of iron and steel.
- **SAP POXY EP- 704** is also used to protect exposed steel reinforcement against rust and to obtain higher bond between steel and concrete.

#### **TECHNICAL DATA :**

- **Solid content** : 80 %.
- **Color** : Grey & colored.
- **Mixing ratio** : 6A: 1 B (by weight).
- **Processing time** : 60 min. 20 °C.
- **Consumption** : 300g / m<sup>2</sup> /coat.

#### **DIRECTIONS FOR USE :**

- The two components of **SAP POXY EP- 704** should be thoroughly mixed together directly prior to application by brush or roller, it is recommended to apply 2 coat of **SAP POXY EP- 704** the second coat to be applied minimum 6 hours after the first coat.

#### **STORAGE LIFE:**

- One year (in closed containers).

#### **PACKAGES:**

- 1 kg and 5 kg in two containers.
- Follow the mixing ratios by weight indicate on the pails.

#### **HEALTH AND SAFETY:**

- Observe the precautionary notices on the label of the container. A material safety data sheet is available upon request & national or local safety regulations should be followed. This product is intended for use by professional applicators.
- As a general rule, avoid skin-and eye contact by wearing overalls, gloves. Goggles mask, etc. Spillage on the skin should immediately be removed by through washing with lukewarm water & soap or a suitable industrial cleaner. Eyes should be flushed with fresh water & medical attention sought immediately.

- Spraying should be carried out under well-ventilated conditions. Avoid inhalation of solvent vapors & paint mist by wearing an air mask.
- This product contains flammable material & should be kept away from spark & open flames.
- Smoking in the area should not be permitted.

*For more information please consult our technical department.*